

3.10 – File share (uploading and downloading)

There are two ways to implement file downloading/uploading. One is using temporary directory for every user. The temporary directory will be deleted after user session was terminated. Another is using permanent directory for each RDP host.

Temporary directory

1. Configure a parent directory in gateway.conf: `tmpdir = C:\\apps\\share`. You can use `${user}` and `${domain}` variables in tmpdir since 5.0. This user directory will not be removed automatically if variables are used in tmpdir.
2. Make sure “Uploading/Downloading files” is selected on client side.

Spark View (RDP) 6.3.0

[Spark View \(VNC\)](#) [Spark View \(SSH\)](#) [Spark View \(TELNET\)](#) [Spark View \(Remote Assistance\)](#) [Spark View \(SMB/SFTP\)](#) [Spark View \(RDP Shadowing\)](#)

Spark Gateway: *default port is 80 if it's not specified (ip:port).

General	Display	Local	Programs	Advanced	Multi-Monitor
Time Zone <input type="text" value="(UTC+01:00) Amsterdam, Berlin, Bern, Rome, Stockholm, Vienna"/>					
Remote audio playback <input type="text" value="Play on this computer"/> Quality <input type="text" value="Low"/>					
Remote audio recording <input type="checkbox"/>					
Choose the devices and resources that you want to use in remote session.					
Clipboard <input checked="" type="checkbox"/> Enable (Copy text, image, html between local and remote)					
Printer <input checked="" type="checkbox"/> Enable; Name <input type="text" value="Remote Printer from Clier"/> <input type="checkbox"/> Text Only (Receipt, Label printers)					
Drives <input checked="" type="checkbox"/> Uploading/Downloading files. (Drag files to your screen after connected).					
Shared Drive Name: <input type="text" value="Cloud Storage"/>					
Camera <input type="checkbox"/> Enable Camera					
USB <input type="checkbox"/> Enable USB					

Permanent directory

1. Configure disk mapping in servers.json:

```
"mapDisk": true,
"disk": [
  {
    "dosName": "Storage",
    "longName": "Long Display Name",
    "devicePath": "/apps/test/"
```

```
}  
1,
```

You can use `${user}` and `${domain}` variables in `devicePath` since 5.0.

2. Make sure "Uploading/Downloading files" is selected on client side.

Uploading files

Choose files or drag files to your remote desktop (anywhere except the cloud icon) after logged in. Click the cloud icon on the top middle of you screen to check the uploading process.

The cloud icon will disappear if you have no operation for a while, click anywhere on the screen to bring it back again.

Downloading files

Click the cloud icon, a file browser dialog will be displayed. You can enter a folder or select a file to download. You can also drag a file to your desktop directly if you are using Chrome.

For best result, please make sure share directory is in another disk or file system.

File share will be disabled if directory is not specified in `servers.json` and `gateway.conf`.

The file which is uploading has ".uploading" filename extension. You can delete it or resume the uploading later. Uploading will be cancelled if there is no enough free space on the drive.

Drag & Drop

You can drag a local file to remote computer if the current application supports file copy and paste, e.g. File Explorer, Desktop etc. you need to set `copyFile = true` in `gateway.conf` to enable this feature. Spark View will ask you to download the files or directories when you copy files or directories in remote computer.

Revision #2

Created 5 April 2022 11:18:06 by Julian

Updated 11 June 2024 12:59:19 by Julian