

2.4 – OAuth2

First, save your OAuth2 provider configuration into a JSON file, for example:

```
{
  "providers" : [{
    "name" : "Google",
    "client_id" : "650561938988-t2r66k1ms3hpoi3kle2g7l2adlarau8s.apps.googleusercontent.com",
    "client_secret" : "-D-nhxWn2E97tZWwLg5IQ6Ak",
    "request_uri" : "https://accounts.google.com/o/oauth2/auth",
    "redirect_uri" : "http://localhost/oauth2callback",
    "access_token_uri": "https://oauth2.googleapis.com/token",
    "auth_uri": "/login_chrome.html",
    "scope": "openid email"
  },
  {
    "name" : "Live",
    "client_id" : "0000000040133A31",
    "client_secret" : "p9WwBr2Pyrq6mtaeZCwTSwqbIF39Br3Z",
    "request_uri" : "https://login.live.com/oauth20_authorize.srf",
    "redirect_uri" : "http://www.remotespark2.com/oauth2callback",
    "access_token_uri": "https://login.live.com/oauth20_token.srf",
    "scope": "wl.emails",
    "profile_uri": "https://apis.live.net/v5.0/me"
  }]
}
```

Second, specify the position of this file in gateway.conf:

```
oauth2 = \\user\\local\\bin\\SparkViewGateway\\oauth2.json
```

For more information, please check the source code of login.html.

Revision #3

Created 8 April 2022 10:45:22 by Guest

Updated 2 August 2023 12:56:51 by Julian