

## 3.5 – Start RemoteApp

Add the following parameters if you want to start the RemoteApp in current browser window:

```
startProgram=app
exe=||WINWORD
directory= encodeURIComponent('C:\\apps\\')
```

### Start RemoteApp in a new window:

```
function startRemoteApp(remoteApp, args, dir, url){
    var r = svManager.getInstance() || new svGlobal.Rdp(url); //reuse existing session if available

    function onSurfaceReady(surface){
        r.addSurface(surface);
        if (r.running()){
            r.startApp(remoteApp, args, dir);
        }else{
            r.run();
        }
    };

    window.svOnSurfaceReady = onSurfaceReady;
    var rail = window.open('rail.html');
    rail.svOnSurfaceReady = onSurfaceReady;
}

window.onload = function() {
    var gateway = 'w-think', //change this to your SparkView address
    server = '192.168.12.132', //change this to your RDP server address
    user = 'vmuser',
    password = 'password',
    remoteApp = '||notepad',
    args = '',
    dir = '',
    url = 'ws://' + gateway + '/RDP?server=' + server + '&startProgram=app' + '&exe=' +
    encodeURIComponent(remoteApp) + '&user=' + user + '&pwd=' + password;
    startRemoteApp(remoteApp, args, dir, url);
}
```

```
};
```

### Checklist:

- Make sure you use the alias name of the RemoteApp and with “||” before the name.
  - Make sure you publish the RemoteApp on your Windows first.
- 

Revision #2

Created 8 April 2022 11:19:04 by Guest

Updated 8 April 2022 11:21:05 by Guest