

4.1 – HTTP API

You can use HTTP request to create a server, symlink dynamically if you don't want to write a plugin for the gateway.

To use the HTTP server, you'll need to configure a password in gateway.conf:

```
Password = yourPassword
```

Then you can use MD5 hash of this password with the HTTP API.

Create servers on gateway:

`http://gatewayAddress/SERVER?id=serverId&displayName=Name&server=hostName&gatewayPwd=passwordInGateway.conf&...`

gatewayPwd is hexadecimal MD5 hash of the password which is configured in gateway.conf.

To delete a server add "&action=delete" to the URL; to update a server, add "&action=update" to the URL.

List servers:

`http://w-think/SERVER?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=ATPlus`

It returns the asked server if id is specified:

```
{"id":"ATPlus","displayName":"ATPlus","server":"cloud.thinrdp.net","shadowing":false,"protocols":"rdp","icon":"kbd.png","rdp":{"username":"demo","password":"demo"}}
```

It returns all servers if id is not specified:

```
{
  "display" : true,
  "type" : "NORMALLIST",
  "cols" : [
    {"name" : "id"},
    {"name" : "displayName"},
    {"name" : "server"},
    {"name" : "remoteProgram"},
  ]
}
```

```
    {"name" : "command"}
  ],
  "rows" : [
    ["ATPlus", "ATPlus", "192.168.12.117", "", ""],
    ["WordPad", "WordPad", "192.168.0.118", "", "wordpad.exe"]
  ]
}
```

Create symlink on gateway:

<http://gatewayAddress/SYMLINK?symlink=symlinkId&server=existingServerId&validTime=20m&gatewayPwd=passwordInGateway.conf&...>

You can also use "validFrom", "validTo" parameters. Please check

<http://www.remotespark.com/view/doc/com/toremove/gateway/connection/SymLink.html> for more information.

To delete a symlink, add "&action=delete" to the URL; to update a symlink, add "&action=update" to the URL.

List symlinks:

<http://w-think/SYMLINK?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&symlink=212a155ee951-40db-95ea-177183174fa7>

It returns the asked symlink if symlink is specified:

```
{"id": "212a155e-e951-40db-95ea-177183174fa7", "resourceId": "169.254.146.243", "validFrom": "Aug 26, 2015 12:00:00 AM", "parameters": ""}
```

It returns all the symlinks if symlink is not specified:

```
{
  "cols": [
    {"name": "id"},
    {"name": "resourceId"},
    {"name": "password"},
    {"name": "validFrom"},
    {"name": "validTime"},
    {"name": "validTo"},
    {"name": "parameters"},
    {"name": "comment"}
  ]
}
```

```
],
"rows": [
  ["212a155e-e951-40db-95ea-177183174fa7", "169.254.146.243", "", 1440568800000, "", 0, "",
""],
  ["c5c6bc9d-f8a7-42ca-af9c-bd28c86adab4", "169.254.146.243", "", 1452544860000, "", 0, "",
""]
]
}
```

List sessions:

[http://w-](http://w-think/SESSION?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=a29575a9-08c2-4162-9bfb-4876820953db)

[think/SESSION?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=a29575a9-08c2-4162-9bfb-4876820953db](http://w-think/SESSION?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=a29575a9-08c2-4162-9bfb-4876820953db)

It returns the single session information if session id is specified:

```
{"id": "a29575a9-08c2-4162-9bfb4876820953db", "server": "192.168.12.118", "clientIp": "169.254.84.132", "clientAgent": "Mozilla
\\5.0 (Windows NT 10.0; WOW64) AppleWebKit\\537.36 (KHTML, like Gecko) Chrome\\47.0.2526.111
Safari\\537.36", "thumbnail": "", "startTime": "Tue Jan 26 15:38:55 MST
2016", "numericId": 621779525, "user": "", "domain": "", "rdpId": 1, "startTime2": 1453847935826}
```

It returns all sessions if session id is not specified:

```
{
  "cols": [
    {"name": "id"},
    {"name": "server"},
    {"name": "clientIp"},
    {"name": "clientAgent"},
    {"name": "startTime"},
    {"name": "numericId"},
    {"name": "user"},
    {"name": "domain"},
    {"name": "join"},
    {"name": "protocol"},
    {"name": "symlink"},
    {"name": "thumbnail"}
  ],
  "size": 1,
```

```
"rows": [
  ["a29575a9-08c2-4162-9bfb-4876820953db", "192.168.12.118", "169.254.84.132", "Mozilla\5.0
(Windows NT 10.0; WOW64) AppleWebKit\537.36 (KHTML, like Gecko) Chrome\47.0.2526.111
Safari\537.36", "Tue Jan 26 15:38:55 MST 2016", 621779525, "", "", "", "RDP", "", ""]
]
```

It returns multiple session information if ids parameter is used:

<http://w-think/SESSION?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=a29575a9-08c2-4162-9bfb-4876820953db&ids=sessinId1,sessionId2>

```
[{session1}, {session2}]
```

Upload license file:

<http://w-think/CONTROL?licenseFile=base64encodedLicenseFile&gatewayPwd=21232f297a57a5a743894a0e4a801fc3>

Please make sure you encode the value of licenseFile. For example:

```
encodeURIComponent(base64encodedLicenseFile)
```

The new license file information will be returned in JSON format if the license file was uploaded successfully.

To query the current license file information, you can use:

<http://w-think/CONTROL?licenseFile=.&gatewayPwd=21232f297a57a5a743894a0e4a801fc3>

Get gateway information

<http://w-think/CONTROL?target=gateway>

```
{"version": "5.8.0", "buildNumber": "941", "buildTime": "2020_03_04_10", "startTime": 1583342850085}
```

Password is not needed for this gateway information request.

Reset Two Factor Authentication

<http://w-think/CONTROL?target=twofa&user=Username&gatewayPwd=21232f297a57a5a743894a0e4a801fc3>

```
curl -k -G --data-urlencode "target=twofa" --data-urlencode "user=svtest\user1"  
https://127.0.0.1/CONTROL
```

Error handling:

HTTP request will return HTTP Status code 500 and {"error:": "error information"} in JSON if there is an error. For example, server or symlink with specified id was not found when you try to get a server or symlink.

HTTP request will return status code 200 if operation succeeded.

Revision #3

Created 8 April 2022 11:24:56 by Guest

Updated 27 May 2022 16:38:37 by Walter