

Appendix A – Integration with symlink use case

Actors:

User, User Portal, Spark Gateway

Preconditions:

User Portal:

- Have user credentials in plain text.

Spark Gateway:

- Configure password in gateway.conf.
- Allow IP addresses of User Portal to access the Spark Gateway API (Optional, [Admin Manual 3.25](#)).
- Create RDP servers with config.html or HTTP API ([Integration Guide 4.1](#)), and make it as a white list.
- Allow symlink access only by setting symlinkOnly = true in gateway.conf. Server id or address will not be allowed to create a connection.
- Disable VNC access by setting vnc = false in gateway.conf (SSH, Telnet are disabled by default).

Basic flow:

1. User login to User Portal.
2. (optional) User Portal create a server on Spark Gateway with HTTP API if that server is not created yet:
`http://gatewayAddress/SERVER?id=serverId&displayName=Name&server=hostName&gatewayPwd=passwordInGateway.conf&...;` Check if server exists:
`http://wthink/SERVER?action=list&gatewayPwd=21232f297a57a5a743894a0e4a801fc3&id=serverId;`
The gateway will return HTTP Status code 500 and {"error": "not found"} in JSON format.
3. User Portal create a symlink on Spark Gateway with HTTP API:
`'http://gatewayAddress/SYMLINK?symlink=symlinkId&server=existingServerId&validTime=8h&gatewayPwd=passwordInGateway.conf¶meters=' +`
`encodeURIComponent('user=domainUser&pwd=domainPassword&domain=domain');`

4. User portal construct a connection link and display it to user:
`http://gateway/rdpdirect.html?symlink=symlinkId&displayName=nameOnBrowserTitle`; or
use the Spark View JS library directly to create a connection:

```
var rdp = new svGlobal.Rdp('wss://gateway/RDP?symlink=symlinkId&..', width, height, color);
```
5. User click the link and connect.
6. User portal delete the symlink when user exist or close the browser:
`http://gatewayAddress/SYMLINK?symlink=symlinkId&action=delete`

Pros:

- Easy and secure.
- Symlink will be invalid or deleted and it cannot be reused by other.
- No need to send the user credential to the browser side.

Cons:

- User domain credentials need to be sent to the gateway in plain text.

Revision #3

Created 8 April 2022 11:45:52 by Guest

Updated 8 April 2022 11:49:16 by Guest